PREFORMED STYROFOAM UTILITY PIPE/CONDUIT WEIGHT CREDIT ~~CRADLE~~ SUPPORT UNIT

by: VICTOR K. SESTOKAS, PE 18 ROUND TOP RD WARREN, NJ 07059 PH NR 908.580.0399 5 NOVEMBER 2002



SECTION I-I (NOT TO SCALE)

NOTES: 1. DIMENSIONS A, B, C AND D ARE A FUNCTION OF ENGINEERING DESIGN FOR THE PARTICULAR APPLICATION.
2. CRADLE IS FORMED TO FIT GEOMETRICAL CROSS-SECTIONAL SHAPE OF CARRIER PIPE/CONDUIT.
3. LENGTH, D, OF CRADLE IS GENERALLY DETERMINED BY CARRIER PIPE/CONDUIT STANDARD LENGTH.
4. DIMENSIONS A, B, C AND D COULD ALSO BE A FUNCTION OF THE DESIRED WEIGHT CREDIT OR (SEE BELOW)



PLAN VIEW (NOT TO SCALE)

4. (CONT'D) REQUIRED BUOYANCY TO CONFORM TO A SPECIFIC ENGINEERING DESIGN
5. THE CRADLE BE DESIGNED FOR MASS PRODUCTION TO CONFORM TO THE MOST COMMON PIPE/CONDUIT TYPES, SIZES AND LENGTHS.
6. THE CRADLE CAN BE DESIGNED FOR DIRECT BURIAL OR GROUND/WATER SURFACE APPLICATIONS.